

Technical Specifications

	3-Series	6-Series					S-Series		
	36	61	62	63	64	67	HD16	HD35	
Max. number of stations / crimp stations	6 / 3	2 / 1	2 / 2	3 / 2	4 / 3	7 / 4	4 / 2	3 / 2	
Wire cross section	26–12 AWG (0.13–4 mm ²)	26–10 AWG (0.13–6 mm ²); optional > 30 AWG (0.05 mm ²)					10–6 AWG (6–16 mm ²)		6–2 AWG (16–35 mm ²)
Max. wire feed rate	26 ft/s (8 m/s)	39 ft/s (12 m/s)					Depends on application		
Stripping length wire end 1	0.004–0.71" (0.1–18 mm)	0.004–0.71" (0.1–18 mm); optional < 1.02" (26 mm)					0.004–0.71" (0.1–18 mm) optional < 1.02" (26 mm)		Max. 1.1" (28 mm)
Stripping length wire end 2	0.004–0.71" (0.1–18 mm)	0.004–0.71" (0.1–18 mm)					0.004–0.71"; (0.1–18 mm)		Max. 1.1" (28 mm)
Min. Wire length Max. 325 ft (99 m)	1.77" (45 mm) optional 1.38" (35 mm)	1.77" (45 mm) opt. 1.38" (35 mm)	2.36" (60 mm); optional 1.38" (35 mm)				2.36" (60 mm) optional 1.38" (35 mm)		4" (100 mm)
Dimensions¹ Width, Depth, Height	W 133" (3.37 m) D 57" (1.46 m) H 70" (1.79 m)	W 139" (3.52 m) D 47" (1.20 m) H 68" (1.73 m)	W 147" (3.74 m) D 51" (1.30 m) H 68" (1.73 m)	W 147" (3.74 m) D 50" (1.27 m) H 73" (1.85 m)	W 147" (3.74 m) D 57" (1.46 m) H 73" (1.85 m)	W 147" (3.74 m) D 74" (1.87 m) H 73" (1.85 m)	W 147" (3.74 m) D 69" (1.76 m) H 95" (2.40 m)	W 155" (3.94 m) D 66" (1.68 m) H 95" (2.40 m)	
Dimensions² Packaging	W 82" (2.08 m) D 65" (1.65 m) H 89" (2.25 m)	W 112" (2.90 m) D 82" (2.10 m) H 91" (2.30 m)					W 112" (2.90 m) D 82" (2.10 m) H 91" (2.30 m)		To be determined
Height Open safety cover	107" (2.72 m)	107" (2.72 m)		112" (2.85 m)			112" (2.85 m)		
Weight Base machine incl. safety cover	970 lb (440 kg)	1014 lb (460 kg)	1036 lb (470 kg)	1300 lb (590 kg)	1312 lb (595 kg)	1378 lb (625 kg)	1411 lb (640 kg)		1521 lb (690 kg)
Weight³ Max. incl. stations and stacker	1654 lb (750 kg)	1482 lb (672 kg)	1638 lb (743 kg)	1969 lb (893 kg)	2046 lb (928 kg)	2540 lb (1152 kg)	2666 lb (1209 kg)		2778 lb (1260 kg)
Weight^{2/3} Shipping	2665 lb (1209 kg)	2615 lb (1186 kg)	2772 lb (1257 kg)	3102 lb (1407 kg)	3179 lb (1442 kg)	4070 lb (1846 kg)	3799 lb (1723 kg)		3924 lb (1780 kg)
Power Supply	3 / N / PE / AC 400/230 V / 50/60 Hz / 16 A (208–480 V with optional transformer)								
Air Supply	Min. 6 bar, oil-free, dried and filtered compressed air								
CE-Conformity	All CrimpCenter models fully comply with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.								
Important Note	For cross sections smaller than 24 AWG (0.22 mm ²), sampling inspection is mandatory. Schleuniger recommends professional application sampling to determine processing capabilities of a particular machine.								

Machines illustrated in this brochure may include optional equipment not fitted as standard. No liability for errors or omissions. Technical specifications are subject to change without prior notice.

¹ Height with closed safety cover, width incl. 2 m stacker

² Gross specifications incl. crate, safety cover, stations and 2 m stacker (stacker for CrimpCenter 67 shipped separately)

³ Weight depends on configuration